




## MRK SERIES SCREWED TYPE DOUBLE RAIL TERMINAL BLOCKS MRK SERİSİ VIDALI TİP ÇİFT KATLI RAY KLEMENSLER



**MRK-C 2,5**  
Order No: 1612

Dimensions Ölçüler (mm)	A	B	C	D	E	F	G
	67,0	61,0	34,5	32,5	32,5	18,0	5,9

### MATERIAL / MATERYAL

Body / Gövde	PA6.6 V2
Bridge / Köprü	Copper / Bakır
Contact / Kontak	CK45 Steel
Screw/ Vida	Steel / Çelik
Temp./ Sıcaklık	-40 °C, +140 °C
Cable Strip L. / Soyma Boyu	9 mm
Torque / Tork	0,4 Nm

DATA / VERİ	TSE / CE	UL
Voltage / Gerilim	500 V	300 V
Current / Akım	24 A	24 A
Section / Kesit	2,5 mm <sup>2</sup>	12 AWG
Norm	EN-60947-7-1	UL 1059

### RENKLER / COLOURS

RENK/COLOUR	Order No. / Sip.No.	Pcs. / Ad.
GREY / GRİ	1612	50
CREAM / KREM	1613	50
BLACK / SİYAH	1614	50
BLUE / MAVİ	1615	50
BROWN/K.RENGİ	1616	50
RED / KIRMIZI	1617	50
YELLOW / SARI	1618	50
GREEN / YEŞİL	1619	50

### ACCESSORIES / AKSESUARLAR

Cross Connection / Köprü	Order No./ Sip. No.	Section/ Kesit	Pcs./ Ad.
	1925	2,5 / 2	100
	1926	2,5 / 3	100
	1927	2,5 / 4	75
	1928	2,5 / 10	30
	1929	2,5 / 20	20
Stopper / Durdurucu	1202,1222,1212		
Group Sticker/Grup Etiketi	1232		
Marking/Markalama	9770 / 4440 / 4442 / 9540 / 7301		
Bridged / Köprülü	1622		
Diode / Diyotlu	1632		
Led / Ledli	1642		